



BROVA

BROVA (DONGGUAN) TECH-CO., LTD.

Add: 428 Changtian Road, Changping Town, Dongguan City,
Guangdong Province,
CHINA.

E-mail: zm@brova.net
jr@brova.net

Tel: +86 138 2377 2390
+86 159 0612 9890

Whatsapp: +86 133 7219 0139

BROVA

ABOUT BROVA

BROVA Tech is a high-quality bicycle frames manufacturer values innovation and practicality along with our development. Now or the future, BROVA will constantly focus on advancing our design, technology and manufacturing to make cycling more enjoyable for everyone. We will strictly obey our corporate culture: assure quality, enhance innovation, improve technology and pursue excellence.

BROVA Tech will make new contributions to the cycling industry.

CORE TECHNOLOGY

- Hydraulic Forging
- Hot Forging
- Anode Process
- Gravity Casting
- Welding
- Painting

BROVA FACTORY - GUANGDONG, CHINA



Construction of our new factory started in late 2022 and is expected to be completed by mid-2024

M9801 MTB SUSPENSION AM

MATERIAL Aluminum #6061
MFG. METHOD Flat welding + Tig pulse
FRAME SIZE 17"
HT ZS56 / ZS56, AZX-578
SEAT POST Φ 31.6
MOTOR BAFANG M600
BATTERY SSE-103 (Sony) 65 cell
REAR HUB 148mmx12 E-thru system
DROPROUT Post Mount
TIRE 29" x2.4" 27.5"*2.8
TRAVEL 160mm
SHOCK LENGTH 230mm / 65mm
SHOCK BUSHING upper 16.8mm / Φ 8, lower 32mm / Φ 8



| ST | TT | HT | CA | SA | FR | OF | BB | RC |
|-------|-----|-----|-----|------|-----|----|-----|-----|
| 15.5" | 618 | 130 | 65° | 71.0 | 564 | 42 | -20 | 464 |

DESCRIPTION

- This is an all mountain category frame that utilizes the 29" platform.
- Combining with RDP four bar suspension, it offers riders maximum confidence and superb handling characteristics.
- BAFANG M600. Fully Inner routing
- SSE-103(Sony) 65 Cell Battery

M9802 MTB SUSPENSION AM

MATERIAL Aluminum #6061
MFG. METHOD Flat welding + Tig pulse
FRAME SIZE 19"
HT ZS56 / ZS56, AZX-578
SEAT POST Φ 31.6
MOTOR BAFANG M600
BATTERY SSE-103 (Sony) 65 cell
REAR HUB 142mmx12 E-thru system
DROPROUT Post Mount
TIRE 29" x2.4"
TRAVEL 140mm
SHOCK LENGTH 190mm / 45mm
SHOCK BUSHING upper 31.5mm / Φ 8, lower 24mm / Φ 8



| ST | TT | HT | CA | SA | FR | OF | BB | RC |
|-----|-----|-----|-----|----|-----|----|-----|-----|
| 19" | 616 | 140 | 67° | 73 | 550 | 42 | -20 | 464 |

DESCRIPTION

- This is an all mountain category frame that utilizes the 29" platform.
- Combining with RDP four bar suspension, it offers riders maximum confidence and superb handling characteristics.
- BAFANG M600. Fully Inner routing
- SSE-103(Sony) 65 Cell Battery

M9803 MTB SUSPENSION AM

MATERIAL Aluminum #6061
MFG. METHOD Flat welding + Tig pulse
FRAME SIZE 15.5"
HT ZS56 / ZS56, AZX-578
SEAT POST Φ 31.6
MOTOR Shimano EP801
BATTERY E4COM (Darfon 720WH)
REAR HUB 148mmx12 E-thru system
DROPROUT Post Mount
TIRE 29" x2.6" 27.5"*2.8
TRAVEL 160mm
SHOCK LENGTH 230mm / 65mm
SHOCK BUSHING upper 16.8mm / Φ 8, lower 32mm / Φ 8



| ST | TT | HT | CA | SA | FR | OF | BB | RC |
|------|-----|-----|-----|------|-----|----|-----|-----|
| 15.5 | 611 | 130 | 65° | 71.0 | 564 | 42 | -20 | 462 |

DESCRIPTION

- This is an all mountain category frame that utilizes the 29" platform.
- Combining with RDP four bar suspension, it offers riders maximum confidence and superb handling characteristics.
- Shimano EP801; Fully inner routing
- E4COM (DARFON 720WH)

BROVA

M9804 MTB SUSPENSION AM

| | |
|---------------|------------------------------|
| MATERIAL | 6061 |
| MFG. METHOD | Flat welding + Tig pulse |
| FRAME SIZE | 19" |
| HT | ZS56 / ZS56, AZX-578 |
| SEAT POST | Φ31.6 |
| MOTOR | BOSCH SX |
| BATTERY | BES3 500WH/625WH/750WH |
| REAR HUB | 148mmx12 E-thru system |
| DROPROUT | Post Mount |
| TIRE | 29"x2.6" 27.5"x2.8" |
| TRAVEL | 140mm |
| SHOCK LENGTH | 190mm / 45mm |
| SHOCK BUSHING | upper 17mm/Φ8, lower 32mm/Φ8 |



| ST | TT | HT | CA | SA | FR | OF | BB | RC |
|-----|-----|-----|-----|----|-----|----|-----|-----|
| 19" | 650 | 140 | 67° | 73 | 550 | 42 | -20 | 475 |

DESCRIPTION

- This is an all mountain category frame that utilizes the 29" platform.
- Combining with RDP four bar suspension, it offers riders maximum confidence and superb handling characteristics.
- Fully inner routing
- Advanced Motor :BOSCH SX
- Compatibility :BES3 500WH/625WH/750WH

M9806 MTB SUSPENSION AM

| | |
|---------------|--------------------------------|
| MATERIAL | A356+6061 |
| MFG. METHOD | Flat welding + Tig pulse |
| FRAME SIZE | 17" |
| HT | ZS56 / ZS56, AZX-578 |
| SEAT POST | Φ31.6 |
| MOTOR | BOSCH G4 |
| BATTERY | BES3 500WH/625WH/750WH |
| REAR HUB | 148mmx12 E-thru system |
| DROPROUT | Post Mount |
| TIRE | 29"x2.6" 27.5"x2.8" |
| TRAVEL | 160mm |
| SHOCK LENGTH | 230mm / 65mm |
| SHOCK BUSHING | upper 16.8mm/Φ8, lower 32mm/Φ8 |



| ST | TT | HT | CA | SA | FR | OF | BB | RC |
|-------|-----|-----|-----|------|-----|----|----|-----|
| 15.5" | 618 | 130 | 65° | 71.0 | 564 | 42 | 20 | 464 |

DESCRIPTION

- This is an all mountain category frame that utilizes the 29" platform.
- Combining with RDP four bar suspension, it offers riders maximum confidence and superb handling characteristics.
- BOSCH G4 Fully Inner routing
- BES3 750WH Battery

M9805 MTB HARDTAIL

| | |
|-------------|------------------------|
| MATERIAL | Aluminum #6061 |
| MFG. METHOD | Tig pulse |
| FRAME SIZE | 19" |
| HT | 1-1/8" / 1-1/8" |
| SEAT POST | Φ31.6 |
| MOTOR | BOSCH G4 |
| BATTERY | BES3 500WH/625WH/750WH |
| REAR HUB | 135mm QR System |
| DROPROUT | Post Mount |
| TIRE | 29"x2.3" |



| ST | TT | HT | CA | SA | FR | OF | BB | RC |
|-----|-----|-----|-----|----|-----|----|-----|-----|
| 19" | 630 | 175 | 68° | 73 | 520 | 42 | -60 | 475 |

DESCRIPTION

- This is an all mountain category frame that utilizes the 29" platform.
- BOSCH G4.
- BES3 500WH/625WH/750WH